

IN THE CLAIMS

Please amend the claims to read as follows:

Listing of Claims

1. (Previously Presented) A method of switching for carrying out switchover, on a radiofrequency landing system of an aircraft, between at least:

a first input of a radiofrequency receiver of the radiofrequency landing system, which input is connected to a first antenna disposed on a lower part of the aircraft and receives a first signal; and

a second input of the radiofrequency receiver of the radiofrequency landing system, which input is connected to a second antenna disposed on an upper part of the aircraft and receives a second signal, wherein:

on initialization, switchover occurs to the input whose signal exhibits the highest level;

after the initialization phase:

a first value of a parameter, in relation to the aircraft, and a second value of this same parameter, in relation to the runway, is determined;

the difference between these first and second values is computed; and

switchover occurs to one of said first and second inputs, as a function of this difference; and at least one hysteresis loop around the switching values is provided.

2. (Original) The method as claimed in claim 1, wherein said parameter is the azimuth.

3. (Canceled).

4. (Previously Presented) The method as claimed in claim 2, wherein if, on initialization, the two inputs exhibit the same signal level, switchover occurs to said first input.

5. (Previously Presented) The method as claimed in claim 2, wherein a value of azimuth of the aircraft is determined on the basis of the signal received and this value of azimuth is compared to predetermined first and second values, and wherein:

when this value of azimuth lies between said predetermined first and second values, a first mode of switchover is implemented; and

when this value of azimuth is less than or equal to said first value or greater than or equal to said second value, a second mode of switchover is implemented.

6. (Previously Presented) The method as claimed in claim 5, wherein, to implement said first mode of switchover:

a first signal level of said first signal emanating from said first antenna is compared to a second signal level recorded; and

when said first signal level is greater than said second signal level, switchover occurs to said first input;

otherwise, said second mode of switchover is implemented.

7. (Previously Presented) The method as claimed in claim 6, wherein said second signal level is obtained by averaging, over a predetermined duration, the signal present on the input to which switchover occurs first.

8. (Previously Presented) The method as claimed in claim 5, wherein, to implement said second mode of switchover, switchover occurs to the input which exhibits the highest signal.

9-11. (Canceled).

12. (Previously Presented) A switching device for carrying out switchover, on a radiofrequency landing system of an aircraft, between at least:

a first input of a radiofrequency receiver of said radiofrequency landing system, which input is for being connected to a first antenna disposed on a lower part of the aircraft and receives a first signal; and

a second input of the radiofrequency receiver of said radiofrequency landing system, which input is for being connected to a second antenna disposed on an upper part of the aircraft and receives a second signal, which device comprises means able to implement the method specified in claim 1.

13. (Previously Presented) An aircraft radiofrequency landing system comprising:

a first antenna, which is disposed on a lower part of the aircraft;

a second antenna, which is disposed on an upper part of the aircraft; and

a radiofrequency receiver comprising;

a first input, which is connected to said first antenna;

a second input, which is connected to said second antenna;

an information processing unit; and

a switching device disposed between said inputs and said information processing unit so as to carry out switchover between said first and second inputs, wherein said switching device is of the type of that specified in claim 12.

14. (New) A method of switching for carrying out switchover, on a radiofrequency landing system of an aircraft, between at least:

a first input of a radiofrequency receiver of the radiofrequency landing system, which input is connected to a first antenna disposed on a lower part of the aircraft and receives a first signal; and

a second input of the radiofrequency receiver of the radiofrequency landing system, which input is connected to a second antenna disposed on an upper part of the aircraft and receives a second signal, wherein:

on initialization, switchover occurs to one of said inputs only if the level of the corresponding signal is sufficient to determine the azimuth of the aircraft;

after the initialization phase:

a first value of an azimuth parameter, in relation to the aircraft, and a second value of this same azimuth parameter, in relation to the runway, is determined;

the difference between these first and second values is computed; and

switchover occurs to one of said first and second inputs, as a function of this difference; and

at least one hysteresis loop around the switching values is provided.